


**COORDINATOR AND ACCESSORIES****COR72 - Coordinator for 72" Opening****COR-72 – Coordinator for 72" Pair****FEATURES**

- Extruded Aluminum Housing.
- Adjustable Tension Override Spring.
- Filler Bar provided allowing an even, unbroken line the full width of the opening.
- Mounting Screws #12 x 24 x 1-1/4" MS.
- For use on Fire Rated Openings.

**SPECIFICATIONS**

**Coordinator** – Coordinator shall be by TA model number COR flat bar type and made from extruded Aluminum. Coordinator shall control the closing sequence so the active door is held open until the inactive door closes, triggering the release of the active door allowing for proper latching. Optional PCOR18, 20 or 32 filler bar shall be provided allowing an even, unbroken line the full width of the opening. Optional PCOR-MB434M or PCOR-MB414N shall be ordered for each piece of hardware to be mounted over the bar coordinator.

**OPTIONS**

TA #	Opening Width	Coordinator Size	Filler Size
<b>COR 60</b>	5'	42"	18"
<b>COR 72</b>	6'	52"	20"
<b>COR 84</b>	7'	52"	32"

- PCOR18 - 18" Filler Bar.
- PCOR20 - 20" Filler Bar.
- PCOR32 - 32" Filler Bar.

**CODE COMPLIANCE**

- ANSI 156.3 Type 21A.
- Conforms to UL10C and UBC 7-2.
- ANSI A117.1 and ADA for barrier-free accessibility.
- C-UBC - California Uniform Builders Code.
- NFPA 80 - National Fire Protection Association.
- NFPA 101 - National Fire Protection, Life Safety .

**1 YEAR WARRANTY**